

SAFETY DATA SHEET

Creation Date 22-Sep-2009 Revision Date 23-Jan-2018 **Revision Number** 6

1. Identification

Product Name Ethynylmagnesium chloride, 0.6M solution in THF/toluene

AC388950000; AC388951000; AC388958000 Cat No.:

Synonyms No information available

Laboratory chemicals. **Recommended Use**

Uses advised against Not for food, drug, pesticide or biocidal product use

Details of the supplier of the safety data sheet

Company

Acros Organics Fisher Scientific One Reagent Lane One Reagent Lane Fair Lawn, NJ 07410 Fair Lawn, NJ 07410

Tel: (201) 796-7100

Emergency Telephone Number

For information **US** call: 001-800-ACROS-01 / Europe call: +32 14 57 52 11 Emergency Number US:001-201-796-7100 / Europe: +32 14 57 52 99 CHEMTREC Tel. No.US:001-800-424-9300 / Europe:001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids Category 2 Substances/mixtures which, in contact with water, emit Category 1

flammable gases

Skin Corrosion/irritation

Category 1 B Category 1

Serious Eye Damage/Eye Irritation Carcinogenicity

Category 2

Reproductive Toxicity Specific target organ toxicity (single exposure)

Category 2 Category 3

Target Organs - Respiratory system, Central nervous system (CNS). Specific target organ toxicity - (repeated exposure)

Category 2

Target Organs - Liver, Kidney.

Category 1

Aspiration Toxicity

Label Elements

Signal Word

Danger

Hazard Statements

Highly flammable liquid and vapor

In contact with water releases flammable gases which may ignite spontaneously

May be fatal if swallowed and enters airways

Ethynylmagnesium chloride, 0.6M solution in THF/toluene

Causes severe skin burns and eye damage
May cause respiratory irritation
May cause drowsiness or dizziness
Suspected of causing cancer
Suspected of damaging the unborn child
May cause damage to organs through prolonged or repeated exposure



Precautionary Statements

Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Do not breathe dust/fume/gas/mist/vapors/spray

Wash face, hands and any exposed skin thoroughly after handling

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep away from any possible contact with water, because of violent reaction and possible flash fire

Handle under inert gas. Protect from moisture

Keep cool

Response

Immediately call a POISON CENTER or doctor/physician

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

Brush off loose particles from skin. Immerse in cool water/wrap with wet bandages

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing **Ingestion**

Do NOT induce vomiting

Rinse mouth

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Store in a dry place. Store in a closed container

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Reacts violently with water

May form explosive peroxides

WARNING. Reproductive Harm - https://www.p65warnings.ca.gov/.

3. Composition/Information on Ingredients

Component	CAS-No	Weight %
Tetrahydrofuran	109-99-9	80-100
Toluene	108-88-3	5-10
Ethynylmagnesium chloride	65032-27-1	5-10

4. First-aid measures

General Advice Show this safety data sheet to the doctor in attendance. Immediate medical attention is

required.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Immediate medical attention is required.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Remove and wash

contaminated clothing before re-use. Call a physician immediately.

Inhalation If not breathing, give artificial respiration. Remove from exposure, lie down. Do not use

mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately. Risk of serious damage to the lungs.

Ingestion Do not induce vomiting. Clean mouth with water. Never give anything by mouth to an

unconscious person. Call a physician immediately. Call a physician or Poison Control

Center immediately. If vomiting occurs naturally, have victim lean forward.

Most important symptoms and

effects

Causes burns by all exposure routes. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Causes central nervous system

depression

Notes to Physician Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media CO 2, dry chemical, dry sand, alcohol-resistant foam. Cool closed containers exposed to fire

with water spray.

Unsuitable Extinguishing Media DO NOT USE WATER

Flash Point Method -No information available

No information available

Autoignition Temperature

Explosion Limits

No information available

Upper No data available
Lower No data available
Sensitivity to Mechanical Impact No information available
Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Reacts violently with water. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Hydrogen chloride gas Carbon monoxide (CO) Carbon dioxide (CO₂) Magnesium oxides

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

Health **Flammability** Instability Physical hazards 3 ۱۸/

Accidental release measures

Personal Precautions

Ensure adequate ventilation. Use personal protective equipment. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental Precautions

Should not be released into the environment. Do not flush into surface water or sanitary sewer system.

Methods for Containment and Clean Keep in suitable, closed containers for disposal. Soak up with inert absorbent material. Do not expose spill to water. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

7. Handling and storage

Handling

Wear personal protective equipment. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe vapors or spray mist. Do not ingest. Do not allow contact with water. If peroxide formation is suspected, do not open or move container. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Storage

Flammables area. Store under an inert atmosphere. Keep away from heat and sources of ignition. Keep away from direct sunlight. Never allow product to get in contact with water during storage. Shelf life 12 months. May form explosive peroxides on prolonged storage. Containers should be dated when opened and tested periodically for the presence of peroxides. Should crystals form in a peroxidizable liquid, peroxidation may have occurred and the product should be considered extremely dangerous. In this instance, the container should only be opened remotely by professionals. Keep containers tightly closed in a dry, cool and well-ventilated place. Corrosives area.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Tetrahydrofuran	TWA: 50 ppm	(Vacated) TWA: 200 ppm	IDLH: 2000 ppm	TWA: 200 ppm
	STEL: 100 ppm	(Vacated) TWA: 590 mg/m ³	TWA: 200 ppm	TWA: 590 mg/m ³
	Skin	(Vacated) STEL: 250 ppm	TWA: 590 mg/m ³	STEL: 250 ppm
		(Vacated) STEL: 735 mg/m ³	STEL: 250 ppm	STEL: 735 mg/m ³
		TWA: 200 ppm	STEL: 735 mg/m ³	_
		TWA: 590 mg/m ³	_	
Toluene	TWA: 20 ppm	(Vacated) TWA: 100 ppm	IDLH: 500 ppm	TWA: 50 ppm
		(Vacated) TWA: 375 mg/m ³	TWA: 100 ppm	TWA: 188 mg/m ³
		Ceiling: 300 ppm	TWA: 375 mg/m ³	_
		(Vacated) STEL: 150 ppm	STEL: 150 ppm	
		(Vacated) STEL: 560 mg/m ³	STEL: 560 mg/m ³	
		TWA: 200 ppm		

Legend

ACGIH - American Conference of Governmental Industrial Hygienists OSHA - Occupational Safety and Health Administration

NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

Engineering Measures Use explosion-proof electrical/ventilating/lighting/equipment. Ensure that eyewash stations

and safety showers are close to the workstation location. Ensure adequate ventilation,

especially in confined areas.

Personal Protective Equipment

Eye/face Protection Wear appropriate protective eyeglasses or chemical safety goggles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166.

Skin and body protection Long sleeved clothing.

Respiratory Protection Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard

EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical State Liquid
Appearance Light brown

Odor No information available Odor Threshold No information available

No information available

Melting Point/RangeNo data availableBoiling Point/RangeNo information available

Flash Point No information available Evaporation Rate No information available

Flammability (solid, gas)

Not applicable

Flammability or explosive limits

Upper No data available
Lower No data available
Vapor Pressure No information available
Vapor Density No information available
Specific Gravity No information available
Solubility Reacts violently with water

Partition coefficient; n-octanol/water No data available

Autoignition TemperatureNo information availableDecomposition TemperatureNo information availableViscosityNo information available

10. Stability and reactivity

Reactive Hazard Yes

Stability May form explosive peroxides. Moisture sensitive. Air sensitive. Light sensitive.

Conditions to Avoid Keep away from open flames, hot surfaces and sources of ignition. Exposure to air.

Incompatible products. Exposure to moist air or water. Exposure to moisture.

Incompatible Materials Acids, Alcohols

Hazardous Decomposition Products Hydrogen chloride gas, Carbon monoxide (CO), Carbon dioxide (CO2), Magnesium oxides

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions

None under normal processing. Reacts violently with water.

11. Toxicological information

Acute Toxicity

Product Information No acute toxicity information is available for this product

Category 4. ATE = 300 - 2000 mg/kg. Based on ATE data, the classification criteria are not Oral LD50

met. ATE > 2000 mg/kg.

Dermal LD50 Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg. Based on ATE data, the classification criteria are not met. ATE > 20 mg/l. Vapor LC50

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation		
Tetrahydrofuran	Tetrahydrofuran 1650 mg/kg (Rat)		180 mg/L (Rat)1 h 53.9 mg/L (Rat)4 h		
Toluene	Toluene > 5000 mg/kg (Rat)		26700 ppm (Rat) 1 h		

Toxicologically Synergistic

Products

No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Causes burns by all exposure routes Irritation

Sensitization No information available

Limited evidence of a carcinogenic effect. The table below indicates whether each agency Carcinogenicity

has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Tetrahydrofuran	109-99-9	Group 2B	Not listed	A3	X	Not listed
Toluene	108-88-3	Not listed				
Ethynylmagnesium chloride	65032-27-1	Not listed				

ACGIH: (American Conference of Governmental Industrial

Hygienists)

A1 - Known Human Carcinogen

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

ACGIH: (American Conference of Governmental Industrial Hygienists)

Mutagenic Effects No information available

Reproductive Effects Suspect reproductive hazard - contains material which may injure unborn child.

Developmental Effects No information available. **Teratogenicity** No information available.

STOT - single exposure Respiratory system Central nervous system (CNS)

STOT - repeated exposure Liver Kidney

Aspiration hazard Category 1

delayed

Symptoms / effects,both acute and Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness,

nausea and vomiting: Causes central nervous system depression

Endocrine Disruptor Information

Component	Component EU - Endocrine Disrupters Candidate List		Japan - Endocrine Disruptor Information	
Tetrahydrofuran	Group III Chemical	Not applicable	Not applicable	

Other Adverse Effects

The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product contains following substances which are hazardous for the environment. Contains a substance which is:. Toxic to aquatic organisms. Reacts with water so no ecotoxicity data for the substance is available.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Tetrahydrofuran	Not listed	2160 mg/l LC50 = 96 h	Not listed	EC50 48 h 3485 mg/l
-		Pimephales promelas		EC50: >10000 mg/L/24h
		Leuciscus idus: LC50: 2820		
		mg/L/48h		
Toluene	EC50: = 12.5 mg/L, 72h	50-70 mg/L LC50 96 h	EC50 = 19.7 mg/L 30 min	EC50: = 11.5 mg/L, 48h
	static (Pseudokirchneriella	5-7 mg/L LC50 96 h		(Daphnia magna)
	subcapitata)	15-19 mg/L LC50 96 h		EC50: 5.46 - 9.83 mg/L, 48h
	EC50: > 433 mg/L, 96h	28 mg/L LC50 96 h		Static (Daphnia magna)
	(Pseudokirchneriella	12 mg/L LC50 96 h		
	subcapitata)			

Persistence and Degradability

Soluble in water Persistence is unlikely based on information available.

Bioaccumulation/ Accumulation

No information available.

Mobility

. Will likely be mobile in the environment due to its water solubility. Is not likely mobile in the environment.

Component	log Pow
Tetrahydrofuran	0.45
Toluene	2.7

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Tetrahydrofuran - 109-99-9	U213	-
Toluene - 108-88-3	U220	-

14. Transport information

DOT

UN-No UN3399

Proper Shipping Name Organometallic substance, liquid, water-reactive, flammable

Proper technical name Tetrahydrofuran, Toluene

Hazard Class 4.3 Packing Group II

TDG

UN-No UN3399

Proper Shipping Name Organometallic substance, liquid, water-reactive, flammable

Hazard Class 4.3 Subsidiary Hazard Class 3 Packing Group II

<u>IATA</u>

UN-No UN3399

Proper Shipping Name Organometallic substance, liquid, water-reactive, flammable

Hazard Class 4.3 Subsidiary Hazard Class 3 Packing Group II

IMDG/IMO

UN-No UN3399

Proper Shipping Name ORGANOMETALLIC SUBSTANCE, LIQUID, WATER-REACTIVE, FLAMMABLE

Hazard Class 4.
Subsidiary Hazard Class 3
Packing Group ||

15. Regulatory information

All of the components in the product are on the following Inventory lists: X = listed

International Inventories

Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
Tetrahydrofuran	Χ	Χ	-	203-726-8	-		Χ	Χ	Χ	Χ	Χ
Toluene	Χ	Χ	-	203-625-9	-		Χ	Χ	Χ	Χ	Χ
Ethynylmagnesium chloride	-		-	-	1		-	Χ	•	-	•

Legend:

- X Listed
- E Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.
- F Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.
- N Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.
- P Indicates a commenced PMN substance
- R Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.
- S Indicates a substance that is identified in a proposed or final Significant New Use Rule
- T Indicates a substance that is the subject of a Section 4 test rule under TSCA.
- XU Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B).
- Y1 Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.
- Y2 Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

U.S. Federal Regulations

TSCA 12(b)

Component	TSCA 12(b)
Tetrahydrofuran	Section 4, 1 % de minimus concentration
SARA 313	

Component	CAS-No	Weight %	SARA 313 - Threshold	
		3	Values %	
Toluene	108-88-3	5-10	1.0	

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act)

CITA (Clean Water Act)				
Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
Toluene	X	1000 lb	X	X

Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Toluene	X		-

OSHA Occupational Safety and Health Administration Not applicable

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
Tetrahydrofuran	1000 lb	-
Toluene	1000 lb 1 lb	-

California Proposition 65

This product contains the following proposition 65 chemicals

Component	CAS-No	California Prop. 65	Prop 65 NSRL	Category
Toluene	108-88-3	Developmental	-	Developmental

U.S. State Right-to-Know

Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Tetrahydrofuran	X	Х	X	-	X
Toluene	X	Х	Х	Х	Х

U.S. Department of Transportation

Reportable Quantity (RQ): N
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade No information available

16. Other information

Prepared By Regulatory Affairs

Thermo Fisher Scientific

Email: EMSDS.RA@thermofisher.com

 Creation Date
 22-Sep-2009

 Revision Date
 23-Jan-2018

 Print Date
 23-Jan-2018

Revision Summary This document has been updated to comply with the US OSHA HazCom 2012 Standard

replacing the current legislation under 29 CFR 1910.1200 to align with the Globally

Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS