MATERIAL SAFETY DATA SHEET



TAM Ceramics, LLC (#220821) 4511 Hyde Park Blvd. P.O. Box 67 Niagara Falls, NY 14305 Phone Number; 716-278-9400 For Chemical Emergency
Spill, Leak, Fire, Exposure or Accident
Call CHEMTREC Day or Night
DOMESTIC NORTH AMERICA 800-424-9300

INTERNATIONAL CALL: 703-527-3887 (collect calls accepted)

IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

Product Name: Ruflux® 61 Milled Rutile 50 Lb Bag Date of Preparation: 01/01/2008

Chemical Name: Rutile Titanium Dioxide

Product code: 1014113

3. COMPOSITION/INFORMATION ON INGREDIENTS				
Components	CAS Number	Weight %	OSHA	ACGIH
Titanium Dioxide	13463-67-7	95 - 99%	15 mg/m ³ TWA	10 mg/m³ TWA
Chromium(III) oxide	1308-38-9	0.1 - 0.5%	0.5 mg/m° TWA (as Cr)	0.5 mg/m° TWA (as Cr)

2. HAZARDS IDENTIFICATION

Emergency Overview

Caution

May cause eye/skin irritation. May cause irritation of respiratory tract. Avoid dust formation.

NFPA 704

Colour:WhiteHealth:1Physical state:Crystalline PowderFire:0Odour:OdorlessInstability:0

Potential Health Effects

Principle routes of exposure: Inhalation, ingestion, skin and eye contact.

Eye contact: Contact with eyes may cause irritation.

Skin contact: Prolonged skin contact may cause skin irritation. Repeated exposure may cause skin dryness or cracking.

Inhalation: Overexposure may cause irritation of the respiratory tract, with symptoms that include coughing, sore throat, and shortness of breath.

Ingestion: May irritate digestive tract.

Chronic toxicity: Excessive inhalation of fumes or dust may cause chemical pneumonitis, cyanosis, and pulmonary edema. Titanium Dioxide is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals.

4. FIRST AID MEASURES

Eye contact: Rinse thoroughly with plenty of water, also under the eyelids. Get medical attention if irritation develops.

Skin contact: Wash off immediately with soap and plenty of water. Get medical attention if irritation develops.

Inhalation: Move to fresh air. If breathing is difficult, give oxygen. If symptoms persist, call a physician.

Ingestion: Drink plenty of water. Do not induce vomiting without medical advice.

Notes to physician: Treat symptomatically.

Product name: Ruflux® 61 Milled Rutile 50 Lb Bag

5. FIRE-FIGHTING MEASURES

Flash point (°C): Non combustible

Suitable extinguishing media: The product itself does not burn. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Hazardous decomposition products: Thermal decomposition can lead to release of irritating gases and vapors.

Special protective equipment for firefighters: As in any fire, wear self-contained breathing apparatus pressure-demand, NIOSH (approved or equivalent) and full protective gear.

Unusual hazards: None known.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Avoid dust formation. Do not breathe vapors/dust. Avoid contact with skin, eyes and clothing. Use personal protective equipment. Ensure adequate ventilation.

Environmental precautions: Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

Methods for cleaning up: Wear personal protective equipment. Use approved industrial vacuum cleaner for removal. Dispose of promptly.

7. HANDLING AND STORAGE

Handling: Handle in accordance with good industrial hygiene and safety practice. Use only in area provided with appropriate exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin, eyes and clothing. Do not eat, drink, or smoke in areas of use or storage.

Storage: Keep in a dry, cool and well-ventilated place.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering measures: Provide appropriate exhaust ventilation at machinery and at places where dust or fumes can be generated.

Respiratory protection: Use NIOSH approved respirator when ventilation is inadequate.

Hand protection: Impervious gloves.

Skin and body protection: Lightweight protective clothing. Keep working clothes separately. Remove and wash contaminated clothing before re-use.

Eye protection: Safety glasses with side-shields.

9. PHYSICAL AND CHEMICAL PROPERTIES

Colour:WhitePhysical state:Crystalline PowderOdour:OdorlessMolecular weight:No data availableBoiling point/range (°C):No data availablepH:No data available

Melting point/range (°C): 1560 - 1840 Specific gravity (Water =1): 3.8 - 4.3

Vapor pressure (mmHg):No data availableEvaporation rate (Water =1):No data availableWater solubility (mg/l):InsolubleVOC content (%)No data available

10. STABILITY AND REACTIVITY

Stability: Stable at normal conditions.

Polymerization: Will not occur.

Hazardous decomposition products: None under normal use.

Materials to avoid: None known.

Conditions to avoid: None known.

11. TOXICOLOGICAL INFORMATION

Acute toxicity: Information given is based on data on the components and the toxicology of similar products.

Chronic toxicity:

In lifetime inhalation studies of rats, airborne respirable size titanium dioxide particles have been shown to cause lung tumors at concentrations associated with substantial particle lung burdens and consequential pulmonary overload and inflammation. However, other laboratory animals such as mice and hamsters did not develop lung tumors under similar testing with titanium dioxide. Human epidemiology studies do not suggest an association between occupational exposure to titanium dioxide and risk for cancer.

Target Organ Effects: Titanium dioxide: Respiratory system.

Titanium Dioxide

OSHA - Select Carcinogens: Listed

IARC - Group 2B: Listed

12. ECOLOGICAL INFORMATION

Aquatic toxicity: Not determined

Persistence and degradability: No information available.

13. DISPOSAL CONSIDERATIONS

Waste from residues / **unused products:** Waste must be disposed of in accordance with federal, state and local environmental control regulations. Where possible recycling is preferred to disposal or incineration.

14. TRANSPORT INFORMATION

DOT (U.S.)

Proper shipping name: Not regulated.

TDG (Canada)

Proper shipping name: Not regulated.

15. REGULATORY INFORMATION

U.S. Regulations:

Not subject to the provisions of SARA 313 Title III

Not subject to TSCA 12(b) Export Notification

State Regulations

This product or its ingredients have been evaluated for New Jersey, Pennsylvania, and California Prop 65 supplier notification requirements. Substances that are subject to notification requirements, if any, are listed below.

Titanium Dioxide
NJRTK: sn 1861

PARTK: Listed (NJRTK)

Canadian WHMIS

Product name: Ruflux® 61 Milled Rutile 50 Lb Bag

WHMIS hazard class: D2A Very toxic materials.

Canadian Ingredient Disclosure List (IDL): Not Listed.

International Inventories

TSCA 8(b): Listed or exempt. Canadian DSL: Listed or exempt. EINECS: Listed or exempt. Phillipines (PICCS): Listed. Japan (ENCS): Listed or exempt.

Korea (KECL): Listed. China (IECS): Listed. Australia (AICS): Listed.

16. OTHER INFORMATION

For Industrial Use Only.

HMIS Health: 1 Fire: 0

Physical hazard: 0

PPE: X

Prepared by: Product Manufacturer, TAM Ceramics, LLC

Disclaimer: The information and recommendations contained in this Material Safety Data Sheet have been compiled from sources believed to be reliable and to represent the most reasonable current opinion on the subject when the MSDS was prepared. No warranty, guaranty or representation is made as to the correctness or sufficiency of the information. The user of this product must decide what safety measures are necessary to safely use this product, either alone or in combination with other products, and determine its environmental regulatory compliance obligations under any applicable federal or state laws.

End of Safety Data Sheet

s