



# Safety Data Sheet

## Dark Green 8000 Series Color Paste

Section 1 : Identification			
<b>Product name :</b> Color paste Dark Green 8000 Series color paste	<b>Others means of identification :</b> Color paste		
<b>Recommended use of the chemical and restrictions on use :</b>  Polyester colorant formulated to be used in composites and fiberglass industry.	<b>Manufacturers:</b>  <table border="0"> <tr> <td style="vertical-align: top;"> <b>Québec</b>            Polynt Composites Canada Inc.            2650, rue Thérèse Casgrain Drummondville            Québec Canada, J2A 4J5            Tel : (819) 477-4516         </td> <td style="vertical-align: top; padding-left: 20px;"> <b>Ontario</b>            Polynt Composites Canada Inc.            29, Regan Road Brampton            Ontario, Canada, L7A 2B2            Tel: (905) 495-0606         </td> </tr> </table>	<b>Québec</b> Polynt Composites Canada Inc. 2650, rue Thérèse Casgrain Drummondville Québec Canada, J2A 4J5 Tel : (819) 477-4516	<b>Ontario</b> Polynt Composites Canada Inc. 29, Regan Road Brampton Ontario, Canada, L7A 2B2 Tel: (905) 495-0606
<b>Québec</b> Polynt Composites Canada Inc. 2650, rue Thérèse Casgrain Drummondville Québec Canada, J2A 4J5 Tel : (819) 477-4516	<b>Ontario</b> Polynt Composites Canada Inc. 29, Regan Road Brampton Ontario, Canada, L7A 2B2 Tel: (905) 495-0606		
<b>EMERGENCY PHONE NUMBER (24h) Canutec : 613-996-6666</b>			

Section 2 : Hazard Identification				
Classification of the substance	Pictograms	Signal words	Hazard statement	Precautionary statement
Combustible Category 4	N.A.	WARNING	<b>H227</b> Combustible liquid	<b>P210</b> Keep away from heat/sparks/open flames/hot surface. No smoking. <b>P233</b> Keep container tightly closed. <b>P235</b> Keep cool. <b>P240</b> Ground/Bond container and receiving equipment. <b>P242</b> Use only non-sparkling tools. <b>P243</b> Take precautionary measures against static discharge.
Category 2  Category 2		WARNING	<b>H315</b> Causes skin irritation  <b>H319</b> (dust) Causes eye irritation	<b>P352 P302</b> Wash skin with soap and water. <b>P352 P302</b> Wash skin with soap and water. <b>P310</b> Seek a doctor.  <b>P337</b> If irritation persists: seek medical advice.  <b>P201</b> Obtain special instruction before use. <b>P202</b> Do not handle until all safety precautions have been read and understood. <b>P260</b> Do not breathe dust/fumes/gas/mist/vapours/sprays <b>P264</b> Wash hands thoroughly after handling. <b>P270</b> Do not eat, drink or smoke when using this product. <b>P272</b> Contaminated work clothing should not be allowed out of the workplace. <b>P280</b> Wear protective gloves/clothing and personal protective equipment. <b>P284</b> Wear respiratory protection.
<b>WHMIS symbols</b>			<b>Other hazards</b>	



# Safety Data Sheet

## Dark Green 8000 Series Color Paste

### Section 3 : Composition /Information on ingredients

Chemical identity of the substance	CAS Number	Percentage ( % )

### Section 4 : First-aid measures

<b>Inhalation</b>	Remove victim to fresh air, give artificial respiration or give oxygen. Call a physician immediately.
<b>Eye contact</b>	Rinse immediately with plenty of water for at least 15 minutes. Remove contact lenses if applicable. Diphoterine type solutions can replace water. A constant feeling of sand grain or persistent redness requires specialized medical advice. Call a physician.
<b>Skin contact</b>	Wash with soap and water. Remove contaminated clothing. If irritation develops, consult a physician. Treat severe redness by Biafine type products. .
<b>Ingestion</b>	Do not induce vomiting, rinse mouth. Consult a physician.

### Section 5 : Fire-fighting measures

<b>Suitable extinguishing media</b> : foam, carbon dioxyde, dry chemicals.
<b>Specific hazards arising from the chemical</b> : On combustion, styrene releases carbon, carbon monoxide and carbon dioxide.
<b>Special protective actions for fire-fighter</b> : Full protective equipment including self-contained breathing apparatus should be used. . Water may be used to cool closed containers to prevent pressure build-up and possible auto-ignition or explosion when exposed to extreme heat.

### Section 6 : Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b> : Remove all sources of ignition (flames, hot surfaces and electrical, static, or friction sparks). Avoid breathing vapours. Ventilate area. Attention ! Contaminated absorbent or used absorbent may heat and ignite a fire. Keep it outside and put some water in the container. Use personnal protection. See section 8.
<b>Environmental precautions</b> : Keep contaminated water far from sewer (Fire-explosion risk) When there is a spill, in presence of water, the styrene will float because specific gravity is lower than water. Styrene is weakly soluble in water. However, styrene has specific gravity lower than 1.
<b>Methods and materials for containment and cleaning up</b> : Contain and remove with inert absorbent and non-sparking tools.

### Section 7 : Handling and Storage

<b>Precautions for safe handling</b> : Do not store above 100°F (37.8°C). Keep away from heat, sparks and flame. Keep containers closed when not in use and upright to prevent leakage. Wash hands after using and before smoking or eating.
<b>Conditions for safe storage</b> : Containers should be grounded when pouring. Wash hands after using and before smoking or eating. Emptied containers may retain hazardous residue and explosive vapours. Keep away from heat, sparks and flames. Do not cut, puncture or weld on or near emptied containers. Follow all hazard precautions given in this data sheet until container is thoroughly cleaned or destroyed. Do not mix residues of this product with any other petroleum wastes. For industrial use and professional application only. ep out of reach of children.



# Safety Data Sheet

## Dark Green 8000 Series Color Paste

### Section 8 : Exposure controls/ personal protection

#### Individual protection measures, such as personal protective equipment (PPE)

**Respiratory protection** : Wear a cartridge or autonomous respirator if the concentration in ppm exceeds recommended exposure standard. These devices, however, require that the user has received appropriate training.

**Skin protection** : Wear long-sleeved overalls or coveralls.

**Gloves**: Wear gloves of butyl or nitrile.

**Eye/face protection** : Use safety eyewear with splash guards or side shields, chemical goggles or face shields.

### Section 9 : Physical and chemical properties

#### Physical properties

**Appearance** : Dark Green viscous liquid

**Odour** : aromatic

**Viscosity** : N/D

#### Chemical properties

**Relative density g/cm cube** : 1.1 à 1.3

**Flash point**  
Pensky-Marten  
(closed cup)

70°C Category 4  
Combustible liquid

### Section 10 : Stability and reactivity

**Reactivity** : The product is not considered self-reactive

**Possibility of hazardous reactions** : Hazardous polymerization : may occur with an exothermic reaction or if in a fire.

**Chemical stability** : Unstable under certain conditions.

**Conditions to avoid** : Elevated temperatures.

**Incompatible materials** : oxidizers, peroxides, strong acids

**Hazardous decomposition products** : acid vapors, carbon dioxide and carbon monoxide.

### Section 11 : Toxicological information

**Information on the likely routes of exposure** : Can be absorbed through the respiratory, digestive, skin and eyes.

**Chronic exposition effects** : Can cause damage to the brain and nervous system such as dizziness, headache and nausea, if continuous exposure.

**Irritation** : May cause lesions to skin, redness and pain in eyes.

**Sensitization**: May rarely cause occupational asthma. Skin sensitization is also very rare.

**Carcinogenicity** : non classified

**Reproductive toxicity** : N.D.

**Mutagenicity** : N.D.

**Interactive effects**: N.D.



# Safety Data Sheet

## Dark Green 8000 Series Color Paste

Section 12 : Ecological information					
<b>Acute aquatic toxicity</b>	<u>Seaweed</u> (Scenedesmus capricornutum) : CEc50	<u>Micro-shellfish</u> (Daphnia magna) : CE50	<u>Fish</u> (Pimephales promelas) : CL50	<u>Bacteria</u> (Pseudomonas fluorescens) : NOEC	<u>Annelides</u> (Eisenia foetida) : CL50
<b>Chronic aquatic toxicity</b>	N.D				
<b>Terrestrial toxicity</b>	N.D.				

Section 13 : Disposal considerations	
<b>Disposal methods</b>	Dispose of in accordance with local, provincial and federal regulations. Do not incinerate closed containers. Incinerate in approved facility. Liquid residue must be treated as hazardous waste and disposed in accordance with environmental regulations.

Section 14 : Transport information	
<b>Proper Shipping Name</b>	N.A.
<b>Placard</b>	N.A.
<b>Transport hazard class(es)</b>	N.A.
<b>UN Number</b>	N.A.
<b>Packing Group</b>	N.A.
<b>Environmental hazards</b>	Not considered as a marine pollutant
<b>Transport in bulk</b>	N.A.
<b>Maximum quantity we can ship considering limited quantity exemption Article 1.17 of Canadian TDG Regulation</b>	N.A.

Section 15 : Regulatory information	
W.H.M.I.S. CLASSIFICATION	Category 4
NFPA CLASSIFICATION (NFPA 30-2008)	Combustible II
National Building Code of Canada	II

Section 16 : Other information
<p>The information contained in this data sheet is given only as a guide. This data sheet had been prepared in good faith using reliable sources. From our point of view, the information is correct, but not guaranteed. The data sheet is non-exclusive as manipulation and use can vary from one application to another. There is no guarantee and Polynt Composites will not be responsible for losses, faults or damages resulting of the use of the information given in this data sheet.</p> <p><b>Last revision : November 18<sup>th</sup>, 2015</b></p>